

Multi-core Cable (braid) 9mm

Geosense Part No
Type

Q10-151
800/T/06/050/PUR/GY/9.0

Specifications

Conductor	
Material	Bare Copper Wires
Conductor No	6
Construction	Twisted Pair 3x2
Stranding	Fine Stranding Class 6
Section	0.5 mm ²
Insulation	
Material	PVC
Colour	Multi
Core Identification	47100 DIN
Shielding	
Screen	Cu Braid - Tinned 85%
Sheath	Fleece Wrap 100%
Jacket	
Diameter	9mm
Material	PUR
Colour	Pebble Grey RAL 7032
Technical	
Weight	129 kg/km
Minimum Bend Radius	6 x diameter
Rated Temperature	-40 to +80°C
Voltage Rating Working	350-500V
Voltage Rating Test	1200V
Conductor Resistance	36Ω/km
Nominal Capacitance C/C	120 nF/km
Nominal Capacitance C/S	160 nF/km
Additional Information	
Compliance	Flame Retardant IEC 60332-1-2



Usage guide

- ~ Tilt Sensor, Analogue 4-20mA, biaxial
- ~ Tilt Sensor, ± 5 Volts, Uniaxial
- ~ In-Place Inclo-Magnetic Extensometer



Specifications may change without prior notice

Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England
www.geosense.co.uk e info@geosense.co.uk t +44(0)1359 270457 f +44(0)1359 272860